

Encoded Protocols Overhead Analysis on Elections

Diogo Becker Christof Fetzer


Faculty of Computer Science, Systems Engineering Group

Bit Flips in Distributed Systems

- Distributed systems typically tolerate crash faults
- Arbitrary faults, *e.g.*, bit flips, occur **surprisingly often**
- Can disrupt large services such as Amazon S3

Problem:

- **■** Cope with bit flips
- Without expensive Byzantine-fault tolerance





A Framework for Distributed Protocols

- Automatically improves the fault coverage of protocols for crash-fault model
- Uses encoding compiler by Schiffel et al.
- Encoded protocols tolerate **non-malicious arbitrary** faults, *e.g.*, bit flips and hardware design faults

Virtualizing Non-malicious Arbitrary Faults

- Errors within shaded area abort process
- Propagated errors invalidate encoding
- Invalid encoding treated as omission/performance failures





Open Questions – Future Work


Current work:

- Overhead of encoding atomic broadcast protocols
- Stronger encoding: use ANB-encoding
- Fault injection: how dangerous are bit flips?

Further research questions:


- How to **partially encode** protocols?
 - Theoretical implications (hybrid models)
 - Performance benefits

Encoding in a Nutshell




- Each 32-bit value encoded in a 64-bit value
- Domain divided in
 - a few valid values (code words)
 - many invalid values (non-code words)
- All operations transformed to support encoding

Overhead Analysis: AN-encoded Elections



- Election time overhead less than 2%
- Doubled CPU overhead, 10 ms heart-beat period
- Absolute CPU utilization less than 5%
- **Low cost for elections**



Assumptions and Fault Models

- No process identifies itself as another process
- No reverse engineering of encoding
- Non-synchronized local clocks available
- Clocks do not fail

Encoding flavors:

ncouning mavors.				
Error	no encoding	AN	ANB	ANBDmer
crash & omission/performance	X	X	X	X
corruption on transmission	X	X	X	X
faulty operation		X	X	X
data corruption		X	X	X
control flow			X	X
address bus on read			X	X
address bus on write				X